POWERHOUSE MODELS

TIMPTE POWERHOUSE

T4K SERIES

Industry-Leading Standard Features

- Aluminum Construction with No Structural Welds
- Thunderstone Mesh Tarp
- (4) Box Mounted D-Rings
- Dual Function Rear Gate (Barn Door/Spreader Combo)
- Large Capacity A-Frame Toolbox
- Spare Tire & Mount
- Rear Stabilizers
- Tarp Tie-Downs
- Safety Bar/Lock
- Serviceable Box Floor

Available Accessories

- 1' Add-Ons for Additional Side Wall Height (3' and 4' Options)
- Dimensional Lumber/Extrusion Holders for Top of Box
- Hydraulic Jack (Easy Swap)
- UHMW Liner
- Solar Panel Charger
- Additional Box Mounted D-Rings
- Additional Removable Stake Pocket D-Rings

STANDARD SPECIFICATIONS	1414 Dump	1416 Dump
GVWR	14,000 lbs.	14,000 lbs.
Empty Weight	Est. 3,460 lbs.	Est. 3,640 lbs.
Payload Capacity	10,540 lbs.	10,360 lbs.
Box Length	14'	16'
Box Inside Width	82"	82"
Overall Width	102"	102"
Box Floor Construction	Fully-Boxed Extrusion with 3/16" Top & 1/8" Bottom	Fully-Boxed Extrusion with 3/16" Top & 1/8" Bottom
Box Side Height	24"	24"
Hoist Type	Dexter Scissor	Dexter Scissor
Rear Gate	Barn door/Spreader Combo	Barn door/Spreader Combo
Tarp	Full-Length Mesh Tarp	Full-Length Mesh Tarp
Wheel Size	16"	16"
Tires	ST235/80R16E - 10 ply	ST235/80R16E - 10 ply
Number of Lug Bolts	8 per wheel (32)	8 per wheel (32)
Axle/Suspension	7,000 lbs. Rubber Torsion	7,000 lbs. Rubber Torsion
Brakes	Electric Self-Adjusting	Electric Self-Adjusting
Coupler	2-5/16" Ball	2-5/16" Ball
Coupler Position	Adjustable	Adjustable
Jack Style	Jost Spring Extended Landing Leg	Jost Spring Extended Landing Leg
Jack Rating	12,000 lbs.	12,000 lbs.
Stake Pockets	4 per side (8 total)	4 per side (8 total)
Lighting	LED	LED