

POWERHOUSE MODELS



**16K
SERIES**



GOOSENECK SYSTEM

Standard Features

Toolbox with Chain Rack

Chain Tray

Spare Tire

Spare Tire Mount

Front Bump Rail

Model	GVW	Usable Deck Size	Empty Weight
1620 GN DO	16,000	20' x 98.25"	Est. 3,460 lbs.
1626 GN DO	16,000	25'-4" x 98.25"	Est. 3,780 lbs.

STANDARD SPECIFICATIONS	1620 GN DO	1626 GN DO
Overall Width	102"	102"
Overall Length	28'-7"	34'-7"
Payload Capacity	12,480 lbs.	12,220 lbs.
Ramp Length	Approx. 4'	Approx. 4'
Tongue Length	96"	96"
Deck Height	35"	35"
Loading Angle	14°	14°
Overall Deck Length	20'	25'-4"
Dovetail Length	60"	60"
Wheel Size	16"	16"
Tires	ST235/80R16E - 10 ply	ST235/80R16E - 10 ply
Number of Lug Bolts	8 per wheel (32)	8 per wheel (32)
Axle/Suspension	7,000 lbs. Rubber Torsion	7,000 lbs. Rubber Torsion
Brakes	Electric Self-Adjusting	Electric Self-Adjusting
Coupler	2-5/16" Ball	2-5/16" Ball
Coupler Position	Adjustable	Adjustable
Jack Style	Dual 12K Jacks	Dual 12K Jacks
Jack Rating	12,000 lbs. each (24,000 lbs. total)	12,000 lbs. each (24,000 lbs. total)
Stake Pockets	12 per side (24 total)	14 per side (28 total)
Lighting	LED	LED